ENVIRONMENTALLY RESPONSIBLE – COLOUR PRINTING FOR YOUR OFFICE.

Professional office colour is provided by the FS-C5150DN for demanding users and small office teams. This compact colour printer saves your office space and fits perfectly in any office environment due to its low noise emissions. It convinces with reduced power consumption, lower emissions and less waste as well as with its integrated duplex unit for double-sided printing. The FS-C5150DN is not only an excellent business decision, it's an excellent choice for the environment, too.

- ▶ Up to 21 pages per minute in A4 in colour and b/w
- ▶ Up to 9,600 dpi printing quality with multibit technology
- Standard duplex unit for double-sided printing
- > 250-sheet universal cassette, also for A6 format
- Up to 4 paper feeders for flexible media support
- Direct Printing from USB flash memory
- Low noise printing, no noise in sleep mode
- Exceptionally low printing costs in its class

Innovative design makes this device easy to operate. Simplified top access ensures fast worry-free toner replacement.



The user-friendly USB host interface is placed at the front of the device. It gives you extra hospitality and easy accessibility for fast and easy document output.









FS-C5150DN

COLOUR PRINTER FOR A4 FORMAT

Ecosys

ECOSYS stands for ECOlogy, ECOnomy and SYStem-printing.

With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly. The modular design concept allows you to add workflowenhancing functions as required. Integrated system software provides long-term cross-network compatibility. KYOCERA's long-life components cost you and the environment less.

PRESCRIBE II

With the KYOCERA page design and control language PRESCRIBE IIc, even complex graphics, logos and forms (multipart forms) can be created independently on the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

The KM NetViewer enables complete monitoring and control of all ECOSYS printers and digital KYOCERA multifunction units from any Windows® PC and thus provides ideal network administration. It also supports the standardised SNMP protocol.

Status Monitor and Command Center The Status Monitor shows the current printer's condition and gives direct access to the Command Center for the modification of settings that are not contained in the drivers (e.g. network settings, adjustment of sleep mode or blocking of the control panel).

USB Host Interface for USB Flash Me

Documents can be printed directly from and scanned to a USB Flash Memory (e.g. USB stick) via the USB host interface. The documents stored as PDF, XPS, TIFF or JPEG are selected directly via the printer's control panel. No computer is required.

Application based profiles

The KX printer driver can create a direct link between dedicated applications and predefined or customized printing profiles. All documents can be printed, for example from MS Outlook, always in monochrome with activated duplex mode resulting in reduced toner and paper consumption.

Technology: KYOCERA ECOSYS, Colour Laser

Engine speed: Up to 21 pages per minute in A4 in colour and b/w Resolution: 600 x 600 dpi

Multibit technology for print quality of up to 9,600 x 600 dpi Duty cycle: Max. 50,000 pages per month

Recommended monthly printing volume: Up to 2,800 pages ** Warm-up time: Approx. 32 seconds or less from power on Time to first page: Approx. 10.5 seconds or less in b/w Approx. 12 seconds or less in colour

Dimensions (W x D x H): Main unit: 390 mm x 523 mm x 370 mm Weight: Main unit: approx. 29.3 kg

Power source: AC 220 ~ 240 V, 50/60 Hz

Power consumption Printing: 360 W Stand-by: 57 W

Sleep-mode: 6 W Noise level (sound pressure level ISO 7779/ISO 9296)

Printing: 50 dB(A) Stand-by: 30 dB(A) Sleep mode: Immeasurably low

Safety standards: GS, TÜV, CE

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity: 50-sheet multi-purpose tray; 60-220 g/m²; A4, A5, A6, B5, B6, Letter, Legal, Custom (70 x 148 mm - 216 x 356 mm) 250-sheet universal cassette; 60-163 g/m²; A4, A5, A6, B5, B6, Letter, Legal, Custom (105 x 148 - 216 x 356 mm) Max. paper capacity incl. options: 1,300 sheets

Duplex functionality as standard

Your KYOCERA Business Partner:

Double-sided printing: 60–163 g/m²; A4, A5, B5, Letter, Legal, Custom (140 x 210 mm - 216 x 356 mm) Output capacity: 250 sheets face-down

CPU: PowerPC 464/667 MHz Memory

Standard: 256 MB RAM, max. 1.280 MB RAM

Standard interfaces: USB 2.0 (Hi-Speed), USB Host Interface dedicated for USB Flash Memory device, FastEthernet (10/100BaseTX) Slot for optional internal print server Slot for optional CompactFlash*-Card

Controller language: PRESCRIBE IIc

Emulations: PCL 6 (5c, XL), KPDL 3 (PostScript* 3 compatible). XPS Direct Print, PDF Direct Print, with automatic emulation sensing

Operating systems: All current Windows operating systems, Mac OS X Version 10.2 or higher, UNIX, LINUX as well as other operating systems on request

Fonts/barcodes: 93 scalable fonts for PCL/PostScript*, 8 fonts for Windows Vista*, 1 bitmap font, 45 barcodes (e.g. EAN8, EAN13, EAN128) with automatic generation of checksums as well as support of two-dimensional barcodes PDF-417 under PRESCRIBE (PCL and other barcodes available as an option)

Integrated accounting: 100 department codes

Toner-Kit TK-580C, TK-580M, TK-580Y: Average continuous cyan, magenta, yellow toner yield 2,800 pages in accordance with ISO/IEC 19798

Starter toner: Average continuous cyan, magenta, yellow toner yield 1,200 pages in accordance with ISO/IEC 19798

Toner-Kit TK-580K: Average continuous black toner yield 3,500 pages in accordance with ISO/IEC 19798 Starter toner: Average continuous black toner yield 1,200 pages in accordance with ISO/IEC 19798

PF-520 Paper feeder: 500 sheets; 60-163 g/m²; A4, A5, B5, Letter, Legal, Custom (148 x 210 mm - 216 x 356 mm) **PF-530 Paper feeder**: 500 sheets; 60–220 g/m²; A4, A5, B5, Letter, Legal, Custom (148 x 210 mm – 216 x 356 mm) CB-520 Cabinet: Wooden desk with storage capacity. Approx. 38.5 cm x 50 cm x 58 cm (WxHxD)

Memory upgrade: MDDR2-256: 256 MB; MDDR2-512: 512 MB, MDDR2-1024: 1.024 MB

CompactFlash*-Card: CF-4: 4 GB (for printing forms, fonts, logos, macro)

USB Flash Memory: Supports direct printing of PDF, XPS, TIFF, JPEG files via USB Host Interface

UG-33: ThinPrint support

Optional interfaces:

PS159: Wireless LAN (802.11b/g) PS1109 Gigabit Ethernet: 10BaseT/100BaseTX/1000BaseT (RJ-45) PS129 Fibre Optic: 100BaseSX (SC) PS1129 Gigabit Fibre Optic: 1000BaseSX (SC)

FS-C5150DN/KL3 FS-C5150DN incl. warranty extension KYOlife 3 years

1-year warranty as standard. KYOCERA guarantees the drums and developers for 3 years or maximum 100,000 pages (whichever occurs sooner), provided the printer is used and cleaned in accordance with the service instructions.

KYOLIFE The up to 3-year on-site warranty extension for printer and options.



KYOCERA MITA Europe B.V. – Branch Office Germany – Otto-Hahn-Straße 12 – 40670 Meerbusch – Germany Tel +49 (0) 2159 928-500 – Fax +49 (0) 2159 918-100 www.kyoceramita-europe.com – info@kyoceramita-europe.com KYOCERA MITA Corporation – 2-28, 1-Chome – Tamatsukuri – Chuo-Ku Osaka 540-8585 – Japan – www.kyoceramita.com

KYOCERA does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged. Based on 36 months' usage.

1010DSEC5150DN_EMC

